1500um Coating Thickness Gage, Fn Type

Part Number: AC-CFN1500B



© Copyright M Gamer Pty. Ltd. 2023

SPECIFICATIONS

Range: 0-1500µm

Resolution: 0.1μm (0-99.9μm) / 1μm (100-1500μm) Accuracy: 2μm (0-100μm / 3%(100-1500μm)

Memory: 30 sets

Power supply: AAA batteries Dimensions: 120×52×26mm

Weight: 170g

Min. measuring area: 25×25mm

Min. curvature: convexity: 5mm; concave: 30mm Min substrate thickness: magnetic material: 0.2mm; non

magnetic material: 0.05mm

SHIPPING WEIGHT: 0.00 Kg

FEATURES

- Integrated Ferrous and Non Ferrous probe
- Ferrous probe is used to measure the thickness of nonmagnetic coatings (zinc, copper, enamel, plastic and so on) on magnetic subtracts (iron, steel)
- Non Ferrous probe is used to measure the thickness of non-conductive coatings (varnish ,enamel, plastic and so on) on conductive subtracts (zinc, copper, aluminum)
- V-type probe for cylindrical work pieces
- Um/mil unit conversion
- Automatic power on/ off
- Back light



Brisbane: (07) 3277 6611 Melbourne: (03) 8773 0333 Perth: (08) 9256 0333 www.gamer.com.au